

### PRODUCT DATA

#### PACKAGING

1 gal cans

#### COVERAGES

~150-250 ft<sup>2</sup> / US gal.

#### COLOR

N/A

#### SHELF LIFE

The shelf life is one (1) year from the date of manufacture in the original, unopened container if properly stored.

#### LIMITATIONS

- Primer must be covered the same day.
- Do not apply over wet surfaces.
- Do not cover wet primer.
- Do not allow product to freeze.

### PRODUCT DESCRIPTION

MK-61 Sheet Membrane Primer is an SBS rubber based primer. It is used to prime surfaces before the application of the MK-62 Sheet Membrane.

### USES

MK-61 is primarily used on all plywood surfaces, prior to the installation of the MK-62 Sheet Membrane, when installing the Shur Deck and Shur Deck Pro Systems.

### ADVANTAGES

- Fast Drying
- Increased Adhesion
- Roll-able
- Economical
- User Friendly

### INSPECTION

Surface must be structurally sound, dry, and free of laitance, oil, grease, curing agents, dirt, dust or other foreign material that may prevent proper adhesion.

### PREPARATION

On plywood, be sure the surface is clean, dry and free of grease, paint, oil, dust or any foreign material that may prevent proper adhesion. Please refer to the desired System Specification Sheet for further information regarding Surface Preparation. Surface should be prepared per industry standard.

### APPLICATION

MK-61 Sheet Membrane Primer should be applied by brush or roller, leaving no puddles. Priming is important, be sure the entire surface to be waterproofed is primed. **DO NOT COVER WET PRIMER.** Prime only as much surface as can be covered with the MK-62 Sheet Membrane in 4 hours. Allow primer to become tacky then apply the MK-62 within 2-4 hours. Primed areas not covered within 4 hours must be re-primed. Please refer to the desired System Specification Sheet for further information regarding Application.

### CAUTION & LIMITATIONS

- The substrate surface must be structurally sound, clean, dry and free of laitance, dirt, dust, oil, grease, paint or other contaminants at the time of material application.
- Substrate and ambient temperature must be above 55°F and below 90°F during and for 24 hours following the application.
- Do not apply in inclement weather, when rain is occurring or expected within 24 hours.
- Designed for professional use.
- Primer must be covered the same day.
- Do not apply over wet surfaces.
- Do not cover wet primer.
- Do not allow any Mer-Ko products to freeze.

### STORAGE & HANDLING

Store all materials off the ground in a dry environment at temperatures between 50°F and 90°F and not in direct sunlight. All materials should be stored in compliance with local fire and safety requirements. Always wear proper safety equipment, including particle mask, eye protection and gloves when mixing and/or applying these products.

### HEALTH PRECAUTIONS

Prolonged or repeated skin contact can cause slight skin irritation. Wear rubber gloves and eye protection. Avoid eye contact and prolonged contact with skin. Wash thoroughly after handling. If eye contact occurs, flush with water for 15 minutes. Call a physician immediately.

### DISCLAIMER

Purchaser's sole and exclusive remedy against the manufacturer of Mer-Ko, shall be limited solely to the replacement of any defective material or a payment by the manufacturer in an amount equal to the cost of the original material.