

## SAFETY DATA SHEET

### Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Product Name: Weather Deck Slip Sheet

Product Code: MK-65

#### WESTCOAT SPECIALTY COATING SYSTEMS

4007 Lockridge St  
San Diego, CA 92102

Information Telephone: 800-250-4519

Emergency Telephone: 800-424-9300

### Section 2 - HAZARDS IDENTIFICATION

#### GHS Ratings:

There are no GHS ratings that apply to this product at this time

#### GHS Hazards

There are no GHS hazards that apply to this product at this time

#### GHS Precautions

There are no GHS precautions that apply to this product at this time

### Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS number	Weight Concentration %

No reportable quantities of hazardous materials present

### Section 4 - FIRST AID MEASURES

#### First aid measures for different exposure routes

**INHALATION:** This material is not likely to be hazardous by inhalation. Consult a physician if symptoms develop or persist.

**EYE CONTACT:** Immediately flush eyes with plenty of water for least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

**SKIN CONTACT:** If in contact with solid material, wash with soap and water. Get medical attention if irritation develops or persists. If in contact with molten material, submerge injured area in cold water. Do not attempt to remove material adhering to the skin. Get medical attention.

**INGESTION:** Not a probable route of exposure.

### Section 5 - FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, and Water Fog.

UNUSUAL FIRE AND EXPLOSION HAZARDS: No unusual fire or explosion hazards noted.

SPECIAL FIREFIGHTING PROCEDURES: Avoid using direct streams of water on molten burning material, as it may scatter and spread the fire. Melts in proximity to fires resulting in slippery floors and stairs.

## Section 6 - ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

FOR NON-EMERGENCY PERSONNEL: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

FOR EMERGENCY RESPONDERS: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

## Section 7 - HANDLING AND STORAGE

PRECAUTION FOR SAFE HANDLING: Keep away from heat, flame and strong oxidizing agents.

CONDITIONS FOR SAFE STORAGE: Keep away from heat, sparks and flame. Store in a cool place, protect from sunlight.

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
		Not Established	Not Established

No reportable quantities of hazardous materials present

### Individual protection measures, such as personal protective equipment

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

RESPIRATORY PROTECTION: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

SKIN PROTECTION: Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

EYE PROTECTION: Use safety eyewear to prevent eye contact.

OTHER PROTECTIVE EQUIPMENT: Refer to safety supervisor or industrial hygienist for further information regarding personal protective equipment and its application. Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

HYGIENIC PRACTICES: Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

### Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b> : Solid	<b>Odor</b> : N/A
<b>Odor threshold</b> : N/A	<b>PH</b> : N/A
<b>Melting point</b> : N/A	<b>Boiling point</b> : N/A
<b>Flash Pt(F/C)</b> : N/A	<b>Evaporation rate</b> : N/A
<b>Flammability (solid, gas)</b> : Not determined	<b>LEL/UEL</b> : N/A
<b>Vapor pressure</b> : N/A	<b>Vapor density</b> : N/A
<b>Relative density</b> : 1.10	<b>Solubility</b> : Negligible
<b>Partition coefficient:n- octanol/water</b> :	<b>Autoignition temp</b> : N/A
<b>Decomposition temp</b> : N/A	<b>Viscosity</b> : N/A

### Section 10 - STABILITY AND REACTIVITY

CONDITIONS TO AVOID: Avoid dust-air mixtures or static charge buildup. Avoid contact with incompatible materials such as oxidizing agents or amines.

HAZARDOUS DECOMPOSITION: Material does not decompose at ambient temperatures. Combustion or high heat may produce thermal decomposition products that may include carbon monoxide, carbon dioxide, dense smoke and other toxic vapors.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

INCOMPATIBILITY: Incompatible with strong oxidizing agents, strong acids and strong alkalis.

### Section 11 - TOXICOLOGICAL INFORMATION

#### Mixture Toxicity

#### Effects of Overexposure

EYE CONTACT: Causes eye irritation. Irritating, and may injure eye tissue if not removed promptly.

SKIN CONTACT: Substance may cause slight skin irritation. Low hazard for usual industrial handling or commercial handling by trained personnel.

INHALATION: This material is not likely to be hazardous by inhalation.

INGESTION: Not a likely source of exposure.

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Skin Contact.

**Section 12 - ECOLOGICAL INFORMATION**

**Section 13 - DISPOSAL CONSIDERATIONS**

DISPOSAL INFORMATION: Dispose of material in accordance to local, state, and federal regulations and ordinances . Do not allow to entering waterways, wastewater, soil, storm drains or sewer systems .

**Section 14 - TRANSPORT INFORMATION**

This material is classified for transport as follows:

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
DOT	Non-Regulated Material			

**Section 15 - REGULATORY INFORMATION**

**State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):** WARNING! This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

**CERCLA-SARA Hazard Category:** This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

**Sara Section 313:** This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

**EU Risk Phrases**

**Safety Phrase**

**Section 16 - OTHER INFORMATION**

**Hazardous Material Information System (HMIS)**

<b>HEALTH</b>	<input type="text" value="0"/>	<b>HMIS &amp; NFPA Hazard Rating</b> <b>Legend</b> * = Chronic Health Hazard <b>0 = INSIGNIFICANT</b> <b>1 = SLIGHT</b> <b>2 = MODERATE</b> <b>3 = HIGH</b>
<b>FLAMMABILITY</b>	<input type="text" value="1"/>	
<b>PHYSICAL HAZARD</b>	<input type="text" value="0"/>	
<b>PERSONAL PROTECTION</b>	<input type="text" value=""/>	

Westcoat Specialty Coating Systems believes, to the best of its knowledge, the information contained herein to be

accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. Westcoat Specialty Coating Systems makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.

Date Prepared: 10/11/2023